



SPECIFICATION SHEET

56-426



MAXIDRY® ULTRA LIGHTWEIGHT NITRILE GLOVE, SEAMLESS KNIT NYLON / LYCRA® LINER

- Seamless string knit shell is comfortable and flexible
- Foam nitrile coatings are compatible with light oils and will provide a good grip and excellent abrasion resistance
- Increased resistance to oils via ATG's LiquiTech® technology
- Synthetic coating combined with an industry leading super light seamless knit liner
- Locking cuff ensures the glove doesn't slip on the hand.
- The micro-cup non-slip grip finish allows for a controlled and superior grip in oily and wet applications
- All ingredients used in the manufacturing and construction of this product are compliant with the REACH legislation
- Silicone free

APPLICATIONS

- Precision handling in oily and wet environments
- Engine, power train, gear box, transmission, and shock absorber assembly
- Handling small castings, small components, and parts
- General handling and maintenance

CARE INSTRUCTIONS

Use commercial laundry soap or detergent (do NOT use dry cleaning solutions) Wash in warm to medium hot water, do not exceed 104°F (40° C). Wash for 10 minutes and rinse in cold water. Repeat wash and rinse if soiling is especially heavy. Tumble dry - maximum temperature 140°F (60° C).



TECHNICAL DATA

MATERIAL	Nitrile, nylon, Lycra®				
COLOR	■ Purple / ■ Black				
CUFF STYLE	Extended Cuff				
SIZES	S - XXL				
PACKAGING	12 pairs per dozen, 6 dozen per case				
CASE	20" x 11.8" x 10.8" / 50.8cm x 30cm x 27.4cm				
CASE WEIGHT	S	M	L	XL	XXL
	15.4lbs / 7.0kg	16.5lbs / 7.5kg	17.6lbs / 8kg	18.7lbs / 8.5kg	19.8lbs / 9kg
COO	Sri Lanka				

DIMENSIONS (in/cm)


	S	M	L	XL	XXL
A	9.8 / 25.0	9.8 / 25.0	9.8 / 25.0	9.8 / 25.0	9.8 / 25.0
B	3.2 / 8.2	3.3 / 8.4	3.7 / 9.4	3.8 / 9.7	3.9 / 10.0
Thickness: 1.1 mm					
Inner Cuff Color					
	S	M	L	XL	XXL
	□ White	■ Green	■ Brown	■ Yellow	■ Ash

PERFORMANCE PROPERTIES

EN388: 4111						
ABRASION	0	1	2	3	4	-
CUT	0	1	2	3	4	5
TEAR	0	1	2	3	4	-
PUNCTURE	0	1	2	3	4	-

BARCODES

ITEM	BAG	DOZEN	CASE
■ 56-426/S	---	01616314117137	02616314117150
■ 56-426/M	---	01616314117120	02616314117143
■ 56-426/L	---	01616314117113	02616314117112
■ 56-426/XL	---	01616314117144	02616314117129
■ 56-426/XXL	---	01616314117151	02616314117136



PROTECTIVE INDUSTRIAL PRODUCTS, INC. | BRINGING THE BEST OF THE WORLD TO YOU®

968 Albany Shaker Road | Latham, NY 12110 | 800-262-5755 | 518-861-0133 | Fax: 518-861-0144 | sales@pipusa.com | www.pipusa.com

This document and the information contained herein is the property of Protective Industrial Products, Inc. (PIP) and may not be used or reproduced without permission. Product users should conduct all appropriate testing or other evaluations to determine the suitability of PIP products for a particular purpose or use within a particular environment. PIP DISCLAIMS ALL WARRANTIES OTHER THAN AS EXPRESSLY PROVIDED.